

KNP NEROLAC

DAMP PROTECT INTERIOR

KNP Nerolac Damp Protect Interior is an acrylic copolymer based, anti-damp and economic undercoat for interior surfaces. It prevents surface dampness from manifesting itself on the top coat and enhances the life of the top coat.



PRODUCT BENEFITS



Provides 10X better waterproofing than ordinary primer



Better hiding and whiteness than ordinary primer



Increases the coverage of the top coat



Prevents surface dampness



Enhances the life of the top coat

APPLICATION AREAS

- Interiors of house

MIXING

- Dilute KNP Nerolac Damp Protect Interior 50% by volume with water and apply it in two coats

COVERAGE

- 200 sq ft/Ltr/coat

DIRECTIONS FOR USE

- Ensure that the surface is properly cleaned and free from any loosely held plaster/powder.
- Make sure that the moisture content in the surface is not more than 40%.
- **Surface preparation:** Clean the surface to ensure that it is free of any dirt and loose particles. Sand the surface with sandpaper 180 and wipe it clean.
- Apply a single coat of KNP Nerolac Damp Protect Interior with a maximum of 50% dilution by volume with water, with a forced coverage of not more than 200 sq ft/L. Allow it to dry for 3-4 hours.
- For a smooth finish of the top coat, apply two thin coats of KNP Nerolac Wall Putty. Allow it to dry for 4-6 hours. Sand with sand paper 180. Wipe it clean.
- Apply a second coat of KNP Nerolac Damp Protect Interior with a maximum of 50% dilution by volume with water, with a forced coverage of not more than 200 sq ft/L. Allow it to dry for 3-4 hours.
- Apply any water based interior painting system over 2nd coat of KNP Nerolac Damp Protect Interior with or without primer.

PRECAUTIONS

- Do not apply when the ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not apply when the humidity is greater than 90%. It may cause prolonged drying-time of the paint and moisture condensation on the walls.
- Do not over dilute.

SHELF LIFE

Best before 24 months from the date of manufacture when kept in a sealed pack and stored under proper conditions.

STORAGE

Keep it in a cool and dry place, out of reach of children.

EHS INFORMATION

Avoid inhalation, eye and skin contact. In case of contact, wash with water and seek medical attention.

Lead content does not exceed 90 parts per million.

Low VOC and no added lead when packed. For VOC content details, refer to the www.knpjapan.com.

DISCLAIMER

KNP JAPAN PVT. LTD. warrants that all products are free from any defects of manufacturing and comply with the specification given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of KNP Nerolac. Purchaser agrees to seek the advice of qualified professionals to carry-out tests and take trials to determine the suitability of products for their intended purpose, prior to full scale usage of KNP Nerolac products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to the replacement of the products or refund of the purchase price paid, if any products is proven defective. No other warranties expressed or implied, shall apply including any warranty of merchantability or fitness for any particular purpose.

KNP JAPAN PVT. LTD. shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

The information supplied in this data sheet is based on our experience through extensive research and is given in good faith in order to help prospective users. We reserve the right to update the information provided in our technical data sheet at any time without prior notice within the scope of technical progress or new developments.

TOLL FREE NO: 9801574444